

All Line Cards

qualitymetalsinc.com/all-line-cards

Copper

Copper					
ASTM B152, Alloy 110, 1/4 to 1/2 hard					
Paper interleaved or PVC protective coating available one side					
Non Pattern Lengths Also Available. Other gages and widths available upon request.					
Gage	Width	96" Length	120" Length	Coil	Lbs. Per Sq. Ft
0.063	36	•		•	2.9
0.094	36	•		•	4.35
0.125	36	•		•	5.8
0.188	36	•		•	8.69
0.250	36	•		•	11.59

Sheet Steel - Aluminized

Sheet Steel - Aluminized						
ASTM A463 CS Type 1						
Light Oil						
Non Pattern Lengths Also Available. Other gages and widths available upon request.						
Gage	Size in Inches	Width	120" Length	Coil	Lbs. Per Sq Ft.	T1-40 Coating
20	0.04	48	•	•	1.61	•
18	0.05	48	•	•	2.11	•

16	0.06	48	•	•	2.61	•
14	0.08	48	•	•	3.24	•
12	0.11	48	•	•	4.49	•

Steel Sheet - Galvanized

Steel Sheet - Galvanized							
ASTM A653 CS Type B							
630, 40, 60, 90 Available							
Chem Treat Dry - no oil ROHS - available on same sizes							
Non Pattern Lengths Also Available. Other gages, widths and coatings available upon request.							
Gage	Width	96" Length	120" Length	Coil	Lbs. Per Sq Ft.	G90 Coating	G40 Coating
28	48	•	•		0.780		•
26	36			•	0.907	•	•
	48		•	•	0.907	•	•
24	48	•	•	•	1.156	•	•
	60		•	•	1.156	•	
22	48		•	•	1.406	•	
	60		•	•	1.406	•	
20	36			•	1.656	•	
	48	•	•	•	1.656	•	
	60		•	•	1.656	•	
18	48	•	•	•	2.156	•	

	60	•	•	•	2.156	•	
16	36	•		•	2.656	•	
	48	•	•	•	2.656	•	
	60		•	•	2.656	•	
14	36			•	3.281	•	
	48		•	•	3.281	•	
	60			•	3.281	•	
12	36			•	4.531	•	
	48		•	•	4.531	•	
	60	•		•	4.531	•	
11	48		•	•	5.156	•	
	60			•	5.156	•	
10	36			•	5.781	•	
	48			•	5.781	•	

Sheet Steel - Galvannealed

Sheet Steel - Galvannealed							
ASTM A653 CS Type B							
Chem Treat Dry - no oil							
Non Pattern Lengths Also Available. Other gages, widths and coatings available upon request.							
Gage	Size in Inches	Width	Length 120"	Coil	Lbs. Per Sq Ft.	A40 Coating	A60 Coating
22	0.0300	48	•	•	1.41	•	

20	0.0400	48	•	•	1.66	•	•
	0.0400	60	•	•	1.66	•	•
18	0.0500	48	•	•	2.16	•	•
	0.0500	60	•	•	2.16	•	•
16	0.0600	48	•	•	2.66	•	•
	0.0600	60	•	•	2.66	•	•
14	0.0800	48	•	•	3.28	•	•
	0.0800	60	•	•	3.28	•	•
12	0.1100	48	•	•	4.53	•	•
	0.1100	60	•	•	4.53	•	•
11	0.1200	60	•	•	5.16	•	•
	0.1200	60	•	•	5.16	•	•
10	0.1400	48	•	•	5.78	•	•
	0.1400	60	•	•	5.78	•	•

Steel Sheet - HRPO

Steel Sheet - HRPO					
ASTM A1011 CS Type B (Commercial Quality Steel)					
Low Carbon Commercial Steel, Pickled, Oiled Milledge					
Non Pattern Lengths Also Available. Other gages and widths available upon request.					
Gage	Width	96" Length	120" Length	Coil	Lbs. Per Sq Ft.
16	48		•	•	2.500

14	36		•	•	3.125
14	48	•	•	•	3.125
14	60		•	•	3.125
14	72		•	•	3.125
13	48		•	•	3.750
12	36	•	•	•	4.375
12	48		•	•	4.375
12	60		•	•	4.375
12	72		•	•	4.375
11	48	•	•	•	5.000
11	60		•	•	5.000
10	36		•		5.625
10	48		•	•	5.625
10	60		•	•	5.625
10	72		•	•	5.625
8	48	•	•	•	6.88
7	60	•	•	•	7.5
0.1875	48		•	•	7.651
0.2500	48		•	•	10.21
0.2500	60		•	•	10.21
0.3750	48	•	•		15.32
0.5000	48		•		20.42

Steel Sheet - CR

Steel Sheet - CR						
ASTM A1008 CS Type B (Commercial Quality Steel)						
Cold Rolled and Annealed, Cut Edge						
Non Pattern Lengths Also Available.						
Gage	Nominal Thickness	Width	96" Length	120" Length	Coil	Lbs. Per Sq Ft.
24	0.0200	48		•		1.000
22	0.0300	48		•	•	1.250
20	0.0400	4	•	•	•	1.500
20	0.0400	60		•	•	1.500
19	0.0400	48		•	•	1.750
18	0.0500	36		•	•	2.000
18	0.0500	48	•	•	•	2.000
18	0.0500	60		•	•	2.000
18	0.0500	72		•	•	2.000
16	0.0600	36		•	•	2.500
16	0.0600	48	•	•	•	2.500
16	0.0600	60		•	•	2.500
16	0.0600	72		•	•	2.500
14	0.0700	36		•	•	3.125
14	0.0700	48	•	•	•	3.125
14	0.0700	60		•	•	3.125

14	0.0700	72		•	•	3.125
13	0.0900	48		•	•	3.750
12	0.1000	36	•	•	•	4.375
12	0.1000	48		•	•	4.375
12	0.1000	60		•	•	4.375
12	0.1000	72		•	•	4.375
11	0.1200	48	•	•	•	5.000
11	0.1200	60		•	•	5.000
10	0.1300	48		•	•	5.625

Stainless Steel Sheet Type 304

Stainless Steel Sheet Type 304								
2B Finish and #3 or 4 Finishes available								
ASTM A240								
Cold Rolled, Annealed. Non-Magnetic								
2B provided paper interleaved. PVC protective coating available one or two sides								
Non Pattern Lengths Also Available. Other gages and widths available upon request.								
Gage	Size in Inches	Width	96" Length	120" Length	Coil	Lbs. Per Sq Ft.	2B	#4
24	0.024	36				1.008		
		48			•	1.008		
22	0.030	36				1.260		

		48		•	•	1.260		
20	0.036	36				1.512		
		48		•	•	1.512		
19	0.042	48				1.764		
18	0.048	36				2.016		
		48		•	•	2.016		
		60		•	•	2.016		
16	0.060	36				2.520		
		48		•	•	2.520		
		60			•	2.520		
14	0.075	36				3.150		
		48		•	•	3.150		
		60			•	3.150		
13	0.090	48				3.780		
12	0.105	36				4.410		
		48		•	•	4.410		
		60			•	4.410		
11	0.120	48		•	•	5.040		
		60			•	5.040		
10	0.135	48		•	•	5.670		
		60			•	5.670		
7	0.187	48			•	7.871		

		60				7.871		
HRAP								
0.19	0.187	48		•		8.579		
0.25	0.25	48		•		11.160		

Aluminum Sheets 6061 T6/T6511

Aluminum Sheets 6061 T6/T6511						
AMS QQ-Q 250/11, ASTM B209 and AMS 4027						
Paper interleaved. PVC protective coating available one side						
Non Pattern Lengths Also Available. Other gages and widths available upon request.						
Gage	Width	96" Length	120" Length	144" Length	Coil	Lbs. Per Sq. Ft
0.040	48			•	•	0.56
0.063	48	•	•	•	•	0.89
0.080	48			•	•	1.13
0.100	48			•	•	1.41
0.125	48			•	•	1.76
0.190	48			•		2.68
0.250	48.5			144.5		3.53
0.375	48.5			144.5		5.29
0.500	48.5			144.5		7.06

Tread Bright Aluminum Sheets 3003 H22

Tread Bright Aluminum Sheets 3003 H22

ASTM B209

Paper interleaving available

Non Pattern Lengths Also Available. Other gages and widths available upon request.

Gage	Width	120" Length	144" Length	Coil	Lbs. Per Sq. Ft
0.063	48	•		•	1.02
0.080	48	•		•	1.21
0.080	60	•		•	1.21
0.100	48	•		•	1.57
0.100	60	•		•	1.57
0.125	48	•		•	1.92
0.125	60	•		•	1.92
0.190	48	•		•	2.82
0.190	60	•		•	2.82
0.250	48	•			3.7

Aluminum Sheets 3003 H14

Aluminum Sheets 3003 H14

AMS QQ-Q 250/11, ASTM B209 and AMS 4027

Paper interleaved. PVC protective coating available one or two sides

Non Pattern Lengths Also Available. Other gages and widths available upon request.

Gauge	Width	96" Length	120" Length	144" Length	Coil	Lbs. Per Sq. Ft
-------	-------	------------	-------------	-------------	------	-----------------

0.032	48		•		•	0.46
0.040	48		•		•	0.71
0.050	48		•		•	0.71
0.063	48		•		•	0.90
0.063	60		•			0.90
0.080	48		•			1.141
0.090	48		•		•	1.29
0.125	48	•	•		•	1.78
0.125	60		•		•	1.78
0.190	48		•		•	2.71
0.190	60		•	•	•	2.71
0.190	72				•	2.71

Aluminum Sheets 5052 H38

Aluminum Sheets 5052 H38					
AMS QQ-Q 250/8, ASTM B209 and AMS 4027					
Paper interleaved. PVC protective coating available one or two sides					
Non Pattern Lengths Also Available. Other gages and widths available upon request.					
Gage	Width	96" Length	120" Length	Coil	Lbs Per Sq. Ft
.040	48		•	•	0.56
.063	30,36,48		•	•	0.88
.080	24,30,36,48,60		•	•	1.12

.100	30,36,48,60		•	•	1.40
.125	30,36,48,60		•	•	1.75

Aluminum Sheets 5052 H32

Aluminum Sheets 5052 H32					
AMS QQ-Q 250/8, ASTM B209 and AMS 4027					
Paper interleaved. PVC protective coating available one or two sides					
Non Pattern Lengths Also Available. Other gages and widths available upon request.					
Gage	Width	96" Length	120" Length	Coil	Lbs. Per Sq. Ft
0.020	48		•	•	0.28
0.025	48		•	•	0.35
0.032	48		•	•	0.45
0.040	48		•	•	0.56
0.050	48		•	•	0.70
0.063	48		•	•	0.88
0.063	60		•	•	0.88
0.063	72		•	•	0.88
0.080	48		•	•	1.12
0.080	60		•	•	1.12
0.080	72		•	•	1.12
0.090	48		•	•	1.26
0.090	60		•	•	1.26

0.090	72		•	•	1.26
0.100	48		•	•	1.40
0.100	60		•	•	1.40
0.125	48		•	•	1.75
0.125	60		•	•	1.75
0.125	72		•	•	1.75
0.190	48		•	•	2.66
0.190	60		•	•	2.66
0.250	48		•	•	3.49
0.250	60		•	•	3.49
0.375	48		144		5.24
0.500	48		144		6.98